

Please type a plus sign (+) inside this box ☐

PTO/SB/05 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL Only for new nonprovisional applications under 37 CFR 1.53(b)	Attorney Docket No.	17201-706	Total Pages	41
	First Named Inventor or Application Identifier			
	Kenneth SOOHOO, "Anti-Aliasing System And Method"			
	Express Mail Label No.	EM089168588 US		

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
---	--

1. ☐ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 29]
(preferred arrangement set forth below)
- Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R&D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure

6. ☐ Microfiche Computer Program *(Appendix)*
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

3. ☒ Drawing(s) (37 CFR 1.152) [Total Sheets 10]
4. ☒ Oath or Declaration (unexecuted) [Total Pages 2]

- a. ☐ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)

[Note Box 5 below]

- i. ☒ **DELETION OF INVENTOR(S)**
 Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference *(useable if Box 4b is checked)*
 The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

8. ☐ Assignment Papers (cover sheet & documents(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document *(if applicable)*
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application, Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)

16. ☐ Other:

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. /

16. CORRESPONDING ADDRESS

☒ Customer Number of Bar Code Label 021971 or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

NAME			
ADDRESS			
CITY	STATE	ZIP CODE	
COUNTRY	TELEPHONE	FAX	

SUBMITTED BY

Typed or
Printed Name

George A. Willman

Signature

George A. Willman

Reg. Number 41,378

Date March 2, 1999

03/02/99
JCS17 U.S. PTO

Application for United States Patent

in the name of

Kenneth Soohoo

ANTI-ALLASING SYSTEM AND METHOD

Attorney Docket No. 17201-706

Express Mail Number EM089168588US

Please direct communications to:

WILSON SONSINI GOODRICH & ROSATI

650 PAGE MILL ROAD

PALO ALTO, CALIFORNIA 94304-1050

650-493-9300

09251081.030299

ANTI-ALIASING SYSTEM AND METHOD

BACKGROUND

Field of the Invention

The invention relates to graphical display, in particular to anti-aliasing for graphical display.

Description of Related Art

5 In graphical user interfaces, shapes are typically displayed as a combination of pixels. Shapes may include text or graphics. A pixel is typically a portion of a display that has a hue, saturation, and luminance value at any particular point in time. Images of text or graphics are created as combinations of pixels throughout the display. A shape to be displayed may in some cases only imperfectly be rendered
10 as a combination of pixels. For example, where a mathematical representation of the shape has a curved edge, pixels in the set of pixels used to render the shape may have edges that do not exactly correspond to the edge of the shape. Thus, in such an example, an imperfect rendering of the mathematical shape occurs. In particular, as characters of text are displayed on a display in a size that is small relative to the size
15 of pixels, imperfections may occur.

One attempt to correct for such imperfections is a technique known as anti-aliasing. Under some anti-aliasing techniques, intensity of a pixel may be adjusted where an edge of the corresponding shape does not correspond to an edge of a pixel.

U.S. Patent No. 5,390,289, entitled "Anti-Alias Font Generation," which is incorporated herein by reference, describes one technique of anti-aliasing for font generation.

SUMMARY OF THE INVENTION

An embodiment of the invention includes a method of displaying a character.

A representation of a character is determined in a bit map having a number of bits greater than a number of pixels in a region of a display in which the character is to be displayed. Based on a relative number of bits that are on in respective portions of the bit map, luminances for corresponding pixels are determined. The character is displayed in the region having the particular number of pixels, and the pixels are displayed with the determined luminances.

In one embodiment of the invention, determining a representation of the character in a bit map includes generating the bit map based on a vector representation of the character. In various embodiments of the invention, the number of bits in the bit map is at least twice as great, at least four times as great, and at least ten times as great as the number of pixels in the region.

According to one embodiment of the invention, the vector representation of the character comprises an Adobe™ character. According to another embodiment of the invention, the vector representation of the character comprises an Adobe Type 1™ character.

09261081.030229

An embodiment of the invention includes a system for displaying a character, and the character is to be displayed within a region of a display having a particular number of pixels. The system includes logic that renders a bit map corresponding to a vector representation of the character. Logic included in the system causes the

5 logic that renders to render a bit map having a number of bits greater than the particular number of pixels. Logic, based on a relative number of bits that are on in respective portions of the bit map, determines luminances for corresponding pixels. Further logic causes the character to be displayed in the region having the particular number of pixels. The pixels are displayed on the display in response to the

10 determined luminances.

According to various embodiments of the invention, the display comprises a television, a color television, a display of a hand held device, a billboard, or other display device.

An embodiment of the invention includes a method for displaying a shape.

15 The shape is to be displayed a particular size on a display. A bit map rendering of the shape is requested in which the shape has a size larger than the particular size. Based on the bit map, luminances are determined for corresponding pixels of a rendering of the shape on the display having the particular size. The shape is displayed on the display in the particular size with the pixels having the determined

20 luminances.

An embodiment of the invention includes a television system. Another embodiment of the invention includes a computer program product.

According to one embodiment of the invention, logic, based on a relative number of bits that are on in respective portions of the bit map, determines an attribute for corresponding pixels. Logic causes the character to be displayed in the region having the particular number of pixels, and the pixels are displayed on the display in response to the determined attributes. According to various embodiments of the invention, the attribute comprises hue, saturation, or luminance.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is illustrated by way of example, and not limitation in the drawings.

FIGs 1A-1D show a character being rendered for display on a display system.

FIG 2 is a block diagram of a system for displaying a character according to an embodiment of the invention.

FIG 3 shows a flow diagram of display of a character according to an embodiment of the invention.

FIG 4A shows a block diagram of a computer system according to an embodiment of the invention.

FIG 4B shows a block diagram of a television system according to an embodiment of the invention.

FIG 4C shows a block diagram of a hand-held device according to an embodiment of the invention.

FIG 5 shows a block diagram of a portion of a bit map and associated pixels according to the embodiment of the invention.

5 FIG 6 shows a block diagram of a portion of a bit map and an associated pixel according to the embodiment of the invention.

09261081.030299

DETAILED DESCRIPTION

The following is a description of embodiments of the invention. The embodiments shown help to illustrate the invention. However, it is not intended that the invention be limited to the precise embodiments shown.

5 In one example of the invention, a shape is rendered on a display as a set of pixels. The luminance of the pixels is determined based on a bit map having a size larger than the size the shape is to be displayed on the display. A shape is rendered in the bit map as various bits in the bit map are either on or off, thus representing whether some portion of the shape is in that part of the bit map. A certain number of
10 bits in the bit map correspond to one pixel. The luminance of the corresponding pixel is determined based on the percentage of bits in the bit map that are on. Thus, the luminance of the pixel helps to represent the extent to which the shape covers the portion of the bit map corresponding to the pixel.

 Thus, where a shape is simply represented as a series of pixels that are either
15 on or off, a rendered shape may not appear as it is intended. Adjusting luminances helps cause the shape appears more accurate, even where the number of pixels may be relatively low. Using a bit map to determine luminances has the advantage of allowing for relatively fast calculation of the luminance. Less CPU power may be used by the system. Also, using such a method to anti-alias a font for display of a
20 character, less storage space may be required because use can be avoided of bit map

fonts that are already anti-aliased. According to an embodiment of the invention, either bit map fonts or outline fonts may be rendered.

FIGs 1A-1D show a character being rendered for display on a display system. FIG 1A shows a depiction of a character 100 according to its ideal shape. Character 100 is bordered by sides including 101, 102, 103, 104, 105, and 106. As shown here, it is depicted true to shape without regard to underlying pixels in grid 107.

FIG 1B shows a rendering of character 110, which corresponds to character 101, in a bit map having a number of bits greater than a number of pixels in a region of the display in which the character is to be displayed. Here, set of columns 122 has twice as many columns (1-12) as columns 142 (1-6) in the corresponding table 140 in FIG 1C. Similarly, set of rows 124 (1-12) includes twice as many rows as rows 144 (1-6) of table 140. Entries of table 140 each are for a pixel. Thus, for each corresponding pixel, the bit map shown in FIG 1B includes four bit values. For example, bits 120 (122, 124, 125, and 126) correspond to table entry 146 of table 140, and table entry 146 corresponds to a single pixel (pixel 152 of FIG 1D).

A percentage value is calculated for each set of bits in the bit map 128 of FIG 4 that corresponds to a pixel of the corresponding portion of the display in which the character is to be displayed. For example, among bits 120, bits 122 and 124 are on, and bits 125 and 126 are off. Thus, 50% of the bits are on, among bits 120. Therefore, the corresponding value 146 in table 140 is 50%. This value of

50% is then used to determine the luminance of the corresponding pixel 152, shown in FIG 1D. For example, luminance of pixel 152 may be half of the luminance that would be used for a pixel corresponding to a portion of a shape that is fully covered by the shape.

5 According to one embodiment of the invention, in a set of 16 bits, the luminance is set to the maximum value when either 15 or 16 of the bits are on. According to various embodiments of the invention, various schemes are used to relate percentage of bits on to luminance. The percentage of bits on or off may be directly converted to a percentage of the maximum luminance. According to other
10 embodiments of the invention, attributes other than luminance, such as hue or saturation, may be adjusted according to the corresponding bits in the bit map.

 Various ratios between the number of bits in the bit map and number pixels in the corresponding set of pixels are possible. For example, according to one embodiment of the invention, the bit map has at least twice as many columns as
15 columns in the corresponding set of pixels. According to another embodiment of the invention, the bit map has at least ten times as many columns as columns in the corresponding set of pixels. According to another embodiment of the invention, the bit map has a number of bits twice as great as the number of pixels in the corresponding set of pixels. According to another embodiment of the invention, the
20 bit map has a number of bits ten times as great as the number of pixels in the corresponding set of pixels.

FIG 2 is a block diagram of a system for displaying a character according to an embodiment of the invention. The system includes an outline module 200, a rendering module 202, a bit map module 204, a luminance module 206, a luminance module 206, and a display module 208. Outline module 200 contains

5 representations of the characters of a font. Such representations may be, for example, Adobe Type 1™ fonts or True Type fonts. According to another embodiment of the invention, the outline module includes information about other shapes other than fonts, such as geometric shapes. Rendering module 202 takes information from outline module 200 to render a representation of the corresponding

10 shape of the font. In response, bit map module 204 creates a bit map. The bit map is a set of bits, which are on or off, according to the shape rendered by rendering module 202. The output of bit map module 204 is provided to luminance module 206, which determines luminances of pixels corresponding to respective sets of bits in the bit map. The result from luminance module 206 is displayed by display

15 module 208.

Outline module 200, rendering module 202, and bit map module 204 may be part of graphics components 210, which, according to one embodiment of the invention, is not particularly adapted to be used with luminance module 206. The system causes graphics components 210 to yield a bit map of a size larger than what

20 is to be displayed by display module 208. Luminance module 206 uses this larger bit map to determine luminances and then provides luminance values for respective

pixels to display module 208 to allow the shape to be displayed in its proper size,
with luminances to account for aliasing of the shape.

According to one embodiment of the invention, graphics components 210 are
replaced by another system that produces a bit map corresponding to a shape.

- 5 Graphics components 210 create the bit maps in a size larger than the size to be
displayed. These larger bit maps are then used to determine pixel values and
respective luminances of the pixels.

FIG 3 shows a flow diagram of display of a character according to an
embodiment of the invention. The string "hello" 302 is displayed according to the
10 method shown. Each character is processed. First, it is determined whether the
character has already been processed and is available in a cache (block 304). If the
character is available in the cache, then proceed to block 312 and display the
character.

If the character is not in the cache, then obtain the outline of the character
15 (block 306). This outline may be obtained, for example, from a module containing
characters of a font such as Adobe Type 1™. Next, render a bit map for a size larger
than the size of the character to be displayed (block 308).

Next, determine luminances of pixels corresponding to respective sets of bits
in the bit map (block 310). Thus, luminances are used to help better depict a shape
20 where the resolution in terms of number of pixels may be low. Varying the
luminance helps to account for where the borders between pixels do not correspond

exactly to the edges of the ideal form of the shape, or character, to be displayed. For example, as described above, a luminance of 50% of the full luminance may be used where only 50% of the ideal shape of the shape would cover the pixel. In an alternative embodiment of the invention, an attribute of the pixel other than
5 luminance is adjusted in response to the corresponding set of bits in the bit map.

Finally, display the character with the pixels having the determined luminances (block 312). After displaying the character, get the next character and continue the process with that character and other characters in string 302.

FIG 4A shows a block diagram of a computer system according to an
10 embodiment of the invention. Computer 500 is coupled to monitor 504.
Computer 500 includes graphics processing and display module 506, which includes anti-aliasing logic 508. Computer 500 also includes Network Interface 507 to couple computer 500 to a network, such as the internet. For example, Network Interface 507 may allow computer 500 to be used to send e-mail. With the help of
15 anti-aliasing logic 508, accordingly to an embodiment of the invention, text 510 is displayed on monitor 504. Text 510 includes character 511 ("M") of the string "Dear Mom 510." The character "M" 511, and other characters of the string 510, are displayed, according to an embodiment of the invention, using anti-aliasing logic 508. Anti-aliasing logic 508, according to an embodiment of the invention,
20 determines luminances for pixels within character 511 based on a particular bit map. In this manner, according to an embodiment of the invention, an improved rendition

of string 510 is achieved. An embodiment of the invention helps to better render shapes, such as characters, where the resolution of the display in terms of numbers in pixels per area is low, however, an attribute of the display may be varied to help better render the shape. The attribute may typically be luminance, such that

5 luminance is made greater or lesser depending on the percentage of the corresponding area of the bit map that is covered by the shape. The attribute may another attribute such as hue, saturation, or other attribute.

FIG 4B shows a block diagram of a television system according to an embodiment of the invention. Electronic system 520 is coupled to television 522.

10 Electronic system 520 includes graphics processing and display 524, which includes anti-aliasing logic 526. Electronic system 520 helps to display string 528 and graphic 530 on television 522. Characters in string 528 ("Best Web Sites!") may be displayed using an anti-aliasing method according to an embodiment of the invention. For example, character "B" 529 may be determined as a bit map larger

15 than the size at which character "B" 529 is to be displayed on television 522. Then, luminances of the corresponding pixels of character "B" 529 are determined based on the relative numbers of bits in the corresponding bit map that are on. Similarly, shape 530 may be displayed according to an embodiment of the invention. For example, circular curve 532 may be displayed as a series of pixels with luminances

20 whose values are calculated based on a bit map larger than the shape 530 to be displayed on television 522. In this way, attributes, such as luminance, may be used

to help compensate for a relatively low resolution of television 522 or other display device.

FIG 4C shows a block diagram of a hand-held device according to an embodiment of the invention. Hand-held device 540 includes graphics processing and display 542 and display 546. Graphics processing and display 542 causes text 548 to be displayed on display 546, according to an embodiment of the invention. Graphics processing and display 542 includes anti-aliasing logic 544, which, according to an embodiment of the invention, helps to display shapes on display 546 through determining attributes of corresponding pixels of display with bit maps.

Text 548 ("STOCK QUOTES ABB BXM") may be rendering according to an embodiment of the invention. For example, for character "Q" 550, first a bit map larger than character "Q" 550 may be determined, and then luminances of pixels corresponding to respective bits in the bit map are then calculated based on the percentage of the bits in the bit map that are on.

Various display devices, for example, a cathode ray tube, liquid crystal display, other light emitting or light reflecting display or other display may be used in combination with various information processing or electronic systems without departing from the spirit of the invention. For example, monitor 504, which is coupled to computer 500, may comprise of a cathode ray tube, liquid crystal display, flat panel display, or other display technology, according to various embodiments of the invention. Electronic system 520 may be integrated with television 522, or may

take the form of a set top box. Computer system 500 may include optional network interface 506, which may be adapted for communication with the Internet or may be specifically adapted for use as a Web browser.

FIG 5 shows a block diagram of a portion of a bit map and associated pixels according to an embodiment of the invention. Set of bits 600 of a bit map includes byte 0 602, byte 1 604, byte 2 606, and byte 3 608.

Set of bits 600 are processed so as to yield two pixels, each having a respective luminance that corresponds to a percentage of bits in respective set of bits. Here, pixels 630 corresponds to the low-order bits (0-3) of byte 0 - byte 3 (i.e., 602, 604, 606, and 608), and pixel 632 corresponds to the high-order bits (bits 4-7) of byte 0 - byte 3. As shown, byte 0 602 is comprised of low order bits 0-3 (610, 612, 614, and 616), and high-order bits 4-7 (618, 620, 622, and 624).

FIG 6 shows a block diagram of a portion of a bit map and a resulting pixel value according to the embodiment of the invention. Through the use of a table, the percentage of bits that are on in high-order bits 701 of set of bits 700 is calculated. For example, high-order bits 704 of byte 702 of set of bits 700 are used as an index into table 760. Column 762 of table 760 corresponds to possible values of high-order bits 704. These values have corresponding values in column 764, which indicate the number of bits that are on in such set of bits. For example, row 712 shows that when the bits 704 have the value "1," then a total of one bit is on. Similarly, row 718 shows that when bits 704 have the value "5," then the total

number of bits that are on is 2. Thus, for high-order bits 704 of byte 702, a number is determined of the number of bits that are on. This number is represented as block 720. Similarly, for high-order bits 724 of byte 722, a number is calculated from table 760 (block 728). Similar calculations are made for high-order bits 732 of byte 730 and high-order bits 742 of byte 740, yielding numbers represented as respective blocks 734 and 744. These numbers (block 720, 728, 734, and 744) are added to yield a number (block 750) which represents the number of bits that are on in set of bits 701.

This number (block 750) relative to the total possible number of bits on in set of bits 701 is used to determine a luminance for the corresponding pixel. An advantage of this configuration that uses a table 760 is that the percentage of bits on in the bit map is calculated relatively rapidly.

Various embodiments of the invention have been illustrated in the figures and have been described in the corresponding text of this application. This foregoing description is not intended to limit the invention to the precise forms disclosed. Rather, the invention is to be construed to the full extent allowed by the following claims and their equivalents.

What is claimed is:

CLAIMS

09251081.030299

1 1. A method of displaying a character, the method comprising:
2 determining a representation of a character in a bit map having a number of
3 bits greater than a number of pixels in a region of a display in which the character is
4 to be displayed;
5 based on a relative number of bits that are on in respective portions of the bit
6 map, determining luminances for corresponding pixels; and
7 displaying the character in the region having the particular number of pixels,
8 the pixels being displayed with the determined luminances.

1 2. The method of claim 1, wherein determining a representation of the
2 character in a bit map includes generating the bit map based on a vector
3 representation of the character.

1 3. The method of claim 2, wherein the vector representation of the
2 character comprises an Adobe™ character.

1 4. The method of claim 2, wherein the vector representation of the
2 character comprises an Adobe Type 1™ character.

1 5. The method of claim 1, wherein the number of bits in the bit map is
2 at least twice as great as the number of pixels in the region.

1 6. The method of claim 1, wherein the number of bits in the bit map is
2 at least four times as great as the number of pixels in the region.

1 7. The method of claim 1, wherein the number of bits in the bit map is
2 at least ten times as great as the number of pixels in the region.

1 8. The method of claim 1, wherein the luminance of a pixel is
2 substantially at a minimum level if substantially all of the bits in the corresponding
3 bit map are on.

1 9. The method of claim 1, wherein the luminance of a pixel is
2 substantially maximum if substantially all of the bits in the corresponding bit map
3 are off.

1 10. The method of claim 1, wherein a respective portion of the bit map
2 includes four sets of 4 bits.

1 11. The method of claim 10, including counting the number of bits that
2 are on in the four sets of 4 bits.

1 12. The method of claim 10, wherein the four sets of four bits comprises
2 four halves of four bytes in a memory.

1 13. The method of claim 1, wherein determining luminances comprises:
2 for at least a subset of bits in a respective portion of the bit map,
3 using a table to determine the number of bits on in the subset, and
4 adding the number of bits on for all subsets of bits in the portion of
5 the bit map.

1 14. The method of claim 13, wherein the subset of bits comprises a byte.

1 15. The method of claim 13, wherein the subset of bits comprises four
2 sequential bits in a byte.

1 16. A system for displaying a character, the character to be displayed
2 within a region of a display having a particular number of pixels, the system
3 comprising:

4 logic that renders a bit map corresponding to a vector representation of the
5 character;
6 logic that causes the logic that renders to render a bit map having a number
7 of bits, the number of bits greater than the particular number of pixels;
8 logic that, based on a relative number of bits that are on in respective
9 portions of the bit map, determines luminances for corresponding pixels; and
10 logic that causes the character to be displayed in the region having the
11 particular number of pixels, the pixels having the determined luminances.

1 17. The system of claim 16, wherein the number of bits in the bit map is
2 at least twice as great as the number of pixels in the region.

1 18. The system of claim 16, wherein the number of bits in the bit map is
2 at least four times as great as the number of pixels in the region.

1 19. The system of claim 16, wherein the number of bits in the bit map is
2 at least ten times as great as the number of pixels in the region.

1 20. The system of claim 16, wherein the vector representation of the
2 character comprises an Adobe™ character.

1 21. The system of claim 16, wherein the vector representation of the
2 character comprises an Adobe Type 1™ character.

1 22. The system of claim 16, wherein a respective portion of the bit map
2 includes at least four sequential bits in a memory.

1 23. The system of claim 16, wherein the logic that determines
2 luminances, for at least a subset of bits in a respective portion of the bit map,
3 uses a table to determine the number of bits on in the subset, and
4 adds the number of bits on for all subsets of bits in the portion of the
5 bit map.

1 24. The system of claim 16, the display comprising a television.

1 25. The system of claim 16, the display comprising a color television.

1 26. The system of claim 16, the display comprising a display of a hand
2 held device.

1 27. The system of claim 16, the display comprising a billboard.

1 28. The system of claim 16, comprising logic for communication with the
2 internet.

1 29. The system of claim 16, comprising web browser logic.

1 30. A method for displaying a shape, the shape to be displayed a
2 particular size on a display, the method comprising:
3 requesting a bit map rendering of the shape in which the shape has a size
4 larger than the particular size;
5 based on the bit map, determining luminances for corresponding pixels of a
6 rendering of the shape on the display having the particular size; and
7 displaying the shape on the display in the particular size with the pixels the
8 determined luminances.

1 31. The method of claim 30, wherein determining luminances comprises
2 counting a number of bits on in a portion of the bit map corresponding to a pixel.

1 32. The method of claim 30, wherein the size larger than the particular
2 size is at least twice as wide as the particular size.

1 33. The method of claim 30, wherein the size larger than the particular
2 size is at least ten times as wide as the particular size.

1 34. The method of claim 30, wherein the shape comprises a character.

1 35. The system of claim 30, the display comprising a television.

1 36. The system of claim 30, the display comprising a color television.

1 37. The system of claim 30, the display comprising a display of a hand
2 held device.

1 38. The system of claim 30, comprising logic for communication with the
2 internet.

1 39. A television system comprising:
2 electronics for displaying images on a display in response to a television
3 signal; and
4 logic for displaying a character, the character to be displayed within a region
5 of the display having a particular number of pixels, the logic comprising:

6 logic that renders a bit map corresponding to a vector representation
7 of the character;
8 logic that causes the logic that renders to render a bit map having a
9 number of bits, the number of bits greater than the particular number of
10 pixels;
11 logic that, based on a relative number of bits that are on in respective
12 portions of the bit map, determines luminances for corresponding pixels; and
13 logic that causes the character to be displayed in the region having the
14 particular number of pixels, the pixels being displayed on the display in
15 response to the determined luminances.

1 40. The system of claim 39, wherein the television signal comprises a
2 terrestrial television broadcast signal.

1 41. The system of claim 39, wherein the television signal comprises a
2 cable television signal.

1 42. The system of claim 39, wherein the number of bits in the bit map is
2 at least twice as great as the number of pixels in the region.

1 43. The system of claim 39, wherein the number of bits in the bit map is
2 at least ten times as great as the number of pixels in the region.

1 44. The system of claim 39, wherein the vector representation of the
2 character comprises an Adobe™ character.

1 45. The system of claim 39, wherein the vector representation of the
2 character comprises an Adobe Type 1™ character.

1 46. The system of claim 39, wherein a respective portion of the bit map
2 includes at least four sequential bits in a memory.

1 47. The system of claim 39, wherein the logic that determines gray levels,
2 for at least a subset of bits in a respective portion of the bit map,
3 uses a table to determine the number of bits on in the subset, and
4 adds the number of bits on for all subsets of bits in the portion of the
5 bit map.

1 48. The system of claim 39, comprising logic for communication with the
2 internet.

09251001.030299

1 49. The system of claim 39, comprising web browser logic.

1 ~~50.~~ A computer program product for displaying a character, the character
2 to be displayed within a region of a display having a particular number of pixels, the
3 computer program product comprising:

4 a computer usable medium having computer readable program code means
5 embodied in the medium, the computer readable program code means having:

6 computer readable program code means for rendering a bit map
7 corresponding to a vector representation of the character;

8 computer readable program code means for causing the logic that
9 renders to render a bit map having a number of bits, the number of bits
10 greater than the particular number of pixels;

11 computer readable program code means for, based on a relative
12 number of bits that are on in respective portions of the bit map, determining
13 luminances for corresponding pixels; and

14 computer readable program code means for causing the character to
15 be displayed in the region having the particular number of pixels, the pixels
16 having the determined luminances.

1 51. The computer program product of claim 50, wherein the number of
2 bits in the bit map is at least twice as great as the number of pixels in the region.

1 52. The computer program product of claim 50, wherein the number of
2 bits in the bit map is at least four times as great as the number of pixels in the region.

1 53. The computer program product of claim 50, wherein the vector
2 representation of the character comprises an Adobe™ character.

1 54. The computer program product of claim 50, comprising computer
2 readable program code means for communication with the internet.

1 55. The computer program product of claim 50, comprising web browser
2 computer readable program code means.

1 56. A system for displaying a character, the character to be displayed
2 within a region of a display having a particular number of pixels, the system
3 comprising:

4 logic that renders a bit map corresponding to a vector representation of the
5 character;

6 logic that causes the logic that renders to render a bit map having a number
7 of bits, the number of bits greater than the particular number of pixels;

8 logic that, based on a relative number of bits that are on in respective
9 portions of the bit map, determines an attribute for corresponding pixels; and
10 logic that causes the character to be displayed in the region having the
11 particular number of pixels, the pixels being displayed on the display having the
12 determined attributes.

1 57. The system of claim 56, wherein the attribute comprises hue.

1 58. The system of claim 56, wherein the attribute comprises saturation.

1 59. The system of claim 56, wherein the attribute comprises luminance.

1 60. The system of claim 56, wherein the number of bits in the bit map is
2 at least twice as great as the number of pixels in the region.

1 61. The system of claim 56, wherein the number of bits in the bit map is
2 at least four times as great as the number of pixels in the region.

1 62. The system of claim 56, wherein the number of bits in the bit map is
2 at least ten times as great as the number of pixels in the region.

1 63. The system of claim 56, wherein the vector representation of the
2 character comprises an Adobe™ character.

1 64. The system of claim 56, the display comprising a television.

1 65. The system of claim 56, comprising logic for communication with the
2 internet.

0951081-030299
662020-18015260

ANTI-ALIASING SYSTEM AND METHOD

ABSTRACT

A method of displaying a character. A representation of a character is determined in a bit map having a number of bits greater than a number of pixels in a region of a display in which the character is to be displayed. Based on a relative number of bits that are on in respective portions of the bit map, luminances for
5 corresponding pixels are determined. The character is displayed in the region having the particular number of pixels, and the pixels are displayed with the determined luminances. A system for displaying a character is disclosed, in which the character is to be displayed within a region of a display having a particular number of pixels. According to various embodiments of the invention, the display comprises a
10 television, a color television, a display of a hand held device, a billboard, or other display device. A method for displaying a shape is described. A method of displaying a shape is disclosed. A television system and a computer program product are disclosed. According to one embodiment of the invention, logic, based on a relative number of bits that are on in respective portions of the bit map,
15 determines an attribute for corresponding pixels. The attribute may comprise luminance, saturation, hue, or other attribute.




Figure 1A

662020-18073260




Figure 1B

62020-18075260

		Column 142					
		1	2	3	4	5	6
Row 144	1			50%	50%		
	2			100%	100%		
	3		25%	25%	25%	25%	
	4		50%	50%	50%	50%	
	5		100%			100%	
	6	75%	25%			25%	75%

146

140

Figure 1C





Figure 1D

**Figure 2**




Figure 3

662020-78079260




Figure 4A




Figure 4B

62201845269




Figure 4C




Figure 5

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of) PATENT APPLICATION
)
Inventor: Kenneth Soohoo)
)
Application No.: Not Yet Assigned)
)
Filed: Herewith (March 2, 1999))
)
Title: **ANTI-ALIASING SYSTEM AND METHOD**)

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name; I believe that I am the original, first and sole inventor (if one name is listed below), first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

ANTI-ALIASING SYSTEM AND METHOD

the specification of which (check applicable ones):

XX is attached hereto;
_____ was filed with the above-identified "Filed" date and "SC/Serial No."
_____ was amended on (or amended through) _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose information which is material to the examination of the application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate as indicated below and have also identified below any foreign application for patent or inventor's certificate on this invention having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	_____ Yes	_____ No
-------------------	--------------------	---------------------------------	--------------	-------------

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulation, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Patented, Pending, Abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

(1) Full name of sole

or first inventor: Kenneth Soohoo

(1) Residence: 908 Bayberry Lane, Redwood Shores, CA

(1) Post Office Address: same

(1) Citizenship: United States of America

(1) Inventor's signature: _____

(1) Date: _____